

Technical Information

The Delkor 22FR520 is a Group 22 maintenance free starting battery. The superior construction qualities include the latest PowerFrame grid technology for significant improvements in durability and performance, vibration resistance and extremely high cranking power. The unrivalled quality of Delkor has seen their Korean manufacturing facility awarded 1st place in the coveted Korean Excellence In Manufacturing Award for 18 consecutive years (2006-2023).

The Delkor 22FR520 is designed to provide years of reliable, trouble free starting for a wide variety of applications including light commercial vehicles, farming and agricultural equipment, 4x4, passenger cars and earthmoving equipment.



Features and Benefits

- Patented PowerFrame grid technology
- Unique high density active material on plates
- Built in hydrometer
- Heat sealed leak proof cover
- Patented liquid & gas separators
- Flame arrestors on vents
- Low resistance envelope separators
- High strength polypropylene case

Applications

Agricultural machinery
Earth Moving Equipment
Light commercial equipment
Passenger cars
4x4

Technical Specifications

Battery Type:	Sealed Maintenance Free	Container Material / Colour:	Polypropylene / Black
Voltage:	12 V	Lid Type / Colour:	Maintenance Free / Black
Capacity (@20hr rate):	60Ah	Grid Type:	PowerFrame
Cold Cranking Amps -18°C, SAE:	520	Separator Type:	Low Resistance Microporous Envelope
Cranking Amps 0°C SAE:		Anti-Vibration:	No
Reserve Capacity:	95 minutes	Assembly Layout:	LH Positive [+ -]
Overall Dimensions:	L 240 x W 172 x H 209	Terminal Type:	SAE
Wet Battery Weight:	15.6 kg	BCI Group:	Group 22