

# SUPER START

## B A T T E R I E S



- Genuine AGM Battery
- Dry Cell (Non-spillable)
- 50% more Cold Cranking Amps
- Superior Design & Quality
- Longer Life
- Australia's Most Powerful & Complete AGM Motorcycle Battery Range

As Australia's largest motorcycle battery distributor, SSB PowerSport has been asked to develop batteries for many applications however one of our most successful and rewarding projects was to develop Australia's most powerful battery for motorcycles that use High Compression V-Twin Motors. These batteries not only require a high CCA (Cold Cranking Amps) but also require a long design life. The result was our SSB DryCell (HVT) battery which has become a First Choice for many Harley Enthusiasts throughout Australia.

With this in mind, we decided to expand our range and make these powerful & long life batteries more accessible and affordable to all riders including road bikes, dirt bikes, quads, Harley's & jet skis. Whether you're a professional or the average rider, we introduce our V-Spec range. Like the name suggests, it is not only one of the few batteries in Australia that is capable battery for bikes with a high compression "V" Twin motors but it is also the best choice in regards cranking power, durability, service life and affordability for all Power Sport applications.

SSB V-Spec batteries are completely spill proof and leak proof and can be used upside down. They are also manufactured using Flame Retardant ABS Plastic making them one of the most versatile and safest motorcycle batteries in Australia.

SSB PowerSport V-Spec batteries are manufactured using state-of-the-art design and construction to produce Australia's most Powerful & Complete range of AGM motorcycle batteries.

These genuine VRLA (Valve Regulated Lead Acid) batteries are manufactured to comply with many Australian and International Standards including Quality Assurance Standard ISO 9001.

With more than 17 years experience, SSB PowerSport is recognized as one of the most reliable and highest quality motorcycle batteries in Australia.

There are over 250 Motorcycle Battery sizes sold in Australia.  
**Cover 99% of your battery sales with just 40 V-Spec AGM Batteries.**

***Don't be fooled by cheap imitations that leak and have no power.***





V-Spec Motorcycle Batteries are available to purchase through most Motorcycle Dealers, Motorcycle Repairers and Motorcycle Part Shops.

### V-Spec High Performance AGM Batteries

Dimensions

Weight

Part Number	Volts	CCA	AH	Length	Width	TH	Terminal Assembly	Terminal Type	with Acid (kg)	Regular Charge
V6N4-2A	6	-	4	70	70	95		Wires	0.90	0.4
V50N18A-A	12	450	21	205	87	162		A	7.30	2.1
V50N18L-A2	12	450	21	205	87	162		A	7.30	2.1
V60N24-A	12	460	30	165	125	175		A	9.90	3.0
VB3L-B	12	85	3	98	56	110		B	1.20	0.3
VB4L-B	12	105	4	120	70	92		A	1.60	0.4
VB5L-B	12	125	5	120	60	130		B	1.90	0.5
VB7B-B	12	175	7	146	60	130		B	2.40	0.7
VB9-B	12	200	9	135	75	139		B	3.10	0.9
VB9L-B	12	200	9	135	75	139		B	3.10	0.9
VB10L-A2	12	235	10	135	90	145		A	3.80	1.0
VB12A-A	12	250	12	135	81	161		B	4.30	1.2
VB14A-A2	12	310	12	135	90	167		A	4.70	1.2
VB14L-A2	12	310	12	135	90	167		A	4.70	1.2
VB16AL-A2	12	310	16	205	71	164		A	5.70	1.6
VB16-B	12	385	19	175	100	155		A	6.50	1.9
VB16CL-B	12	385	19	175	100	175		A	6.60	1.9
VB16L-B	12	385	19	175	100	155		A	6.50	1.9
VB30CL-B	12	460	30	165	125	175		A	9.90	3.0
V51913	12	320	19	186	81	170		G	6.00	1.9
VT4B-4	12	85	2.3	113	38	85		K	0.90	0.2
VT6.5B-3	12	130	6.5	139	66	102		B	2.30	0.6
VT7B-4	12	150	6.5	150	65	93		A	2.30	0.6
VT9B-4	12	200	8	150	68	105		A	2.70	0.8
VT12B-4	12	260	10	150	69	130		A	3.60	1.0
VT14B-4	12	310	12	150	69	145		A	4.10	1.2
VTR4A-BS	12	85	2.3	113	48	85		L	0.90	0.2
VTX4L-BS	12	105	3	113	70	85		A	1.50	0.3
VTX5L-BS	12	195	6	113	70	105		A	2.10	0.6
VTX7A-BS	12	150	6	150	87	93		A	2.50	0.6
VTX7L-BS	12	175	6	113	70	130		A	2.40	0.6
VTX9-BS	12	260	10	150	87	105		A	3.40	1.0
VTX12-BS	12	265	10	150	87	130		A	3.90	1.0
VTX14-BS	12	290	12	150	87	145		A	4.50	1.2
VTX14L-BS	12	290	12	150	87	145		A	4.50	1.2
VTX15L-BS	12	340	13	175	87	130		A	4.70	1.3
VTX16-BS	12	340	14	150	87	161		A	5.10	1.4

VTX20-BS	12	400	18	175	87	155		A	5.90	1.8
VTX20L-BS	12	400	18	175	87	155		A	5.90	1.8
VTZ10-S	12	280	8.6	150	87	93		A	2.90	0.8
VTZ14-S	12	340	11.2	150	87	110		A	3.60	1.1